



# 2017 Front Suspension Specifications

Oil Volume, Air Pressure, Coil Spring Rates, and Configurations



# Oil Volume and Lubricant

		DAMPER						SPRING					
FORK	MODEL	Damper	Upper Tube			Lower Leg		Spring	Upper Tube		Lower Leg		
			RockShox® Suspension Oil	Oil Height* (mm)	Volume (mL)	RockShox Suspension Oil	Volume (mL)		Lubricant	Volume (mL)	RockShox Suspension Oil	Volume (mL)	
30™ Gold	RL 26	Motion Control™	5wt	80-85	85	15wt	5	Solo Air™	5wt	3-6	15wt	10	
	RL 27.5				102								
	RL 29												
30 Silver	TK 26	TurnKey™	5wt	80-85	100	15wt	5	Solo Air	5wt	3-6	15wt	10	
	TK 27.5				123			Solo Air					
	TK 29				122			Coil	Grease Coil Spring	-			
Argyle™	RC	Motion Control	5wt	-	130	15wt	10	Coil	Grease Coil Spring	-	15wt	30	
Bluto™	RCT3	Motion Control	5wt	71-77	106	15wt	5	Solo Air	Grease Air Piston	-	15wt	5	
	RL												
BoXXer®	World Cup	Charger Damper™	3wt	-	Bleed	0w-30	10	Solo Air	Grease Air Piston	-	0w-30	10	
	Team												
	RC	Motion Control IS	5wt	95-104	290			Coil	Grease Coil Spring	-		20	
Domain™	RC	Motion Control IS	5wt	-	200	15wt	10	Coil	Grease Coil Spring	-	15wt	30	
Domain Dual Crown				103-109	325							40	

\*Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

# Oil Volume and Lubricant

		DAMPER						SPRING							
FORK	MODEL	Damper	Upper Tube			Lower Leg		Spring	Upper Tube		Lower Leg				
			RockShox® Suspension Oil	Oil Height* (mm)	Volume (mL)	RockShox Suspension Oil	Volume (mL)		Lubricant	Volume (mL)	RockShox Suspension Oil	Volume (mL)			
Lyrik™	RC2 DH	Mission Control™ DH	5wt	-	184	15wt	10	Solo Air™	Grease Air Piston	-	15wt	10			
	RCT3	Charger Damper™	3wt	-	Bleed	0w-30		Solo Air		-	0w-30	10			
	RC							Dual Position Air™		-	0w-30	10			
Paragon™ Gold	RL	Motion Control™	5wt	80-85	87	15wt	12	Solo Air	5wt	3-6	15wt	12			
Paragon Silver	TK	Turnkey™	5wt	80-85	100	15wt	12	Coil	Grease Coil Spring	-	15wt	12			
Pike®	RCT3	Charger Damper	3wt	-	Bleed	0w-30	10	Solo Air	Grease Air Piston	-	0w-30	10			
	RC							Dual Position Air					-	0w-30	10
	DJ							Solo Air					-	0w-30	10
Reba®	RL	Motion Control	5wt	71-77	106	15wt	5	Solo Air	Grease Air Piston	-	15wt	5			
Recon™ Gold	RL	Motion Control	5wt	80-85	133	15wt	6	Solo Air	5wt	3-6	15wt	6			
	TK	TurnKey						Solo Air					5wt	3-6	15wt
Recon Silver	RL	Motion Control	5wt	80-85	118	15wt	6	Solo Air	5wt	3-6	15wt	6			
	RL BOOST™				140										
	TK 26"	150													
	TK 27.5", 29"	Turnkey			118							Coil	Grease Coil Spring	-	12

\*Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

# Oil Volume and Lubricant

		DAMPER						SPRING				
FORK	MODEL	Damper	Upper Tube			Lower Leg		Spring	Upper Tube		Lower Leg	
			RockShox® Suspension Oil	Oil Height* (mm)	Volume (mL)	RockShox Suspension Oil	Volume (mL)		Lubricant	Volume (mL)	RockShox Suspension Oil	Volume (mL)
Revelation™	RCT3	Motion Control™	5wt	82-88	134	15wt	5	Solo Air™	Grease Air Piston	-	15wt	5
	RL											
RS-1™	-	Accelerator Damper™	5wt	-	Bleed	15wt	5-10	Solo Air	Grease Air Piston	-	15wt	5-10
Sektor™ Gold	RL	Motion Control	5wt	80-85	130	15wt	5-8	Solo Air	5wt	3-6	15wt	3-8
					125			Dual Position Coil™	Grease Coil Spring	-		10-16
Sektor Silver	RL	Motion Control	5wt	80-85	150	15wt	6	Solo Air	5wt	3-6	15wt	6
	RL BOOST™				140							
SID®	RLC	Charger Damper™	3wt	-	Bleed	15wt	5	Solo Air	Grease Air Piston	-	15wt	5
	World Cup											
	RL	Motion Control	5wt	71-77	100							
XX												
XC™ 30	TK	TurnKey™	5wt	80-85	143	-	-	Coil	Grease Coil Spring	-	-	-
Yari™	RC	Motion Control	5wt	100-106	180	0w-30	10	Solo Air	Grease Air Piston	-	0w-30	10
								Dual Position Air™				

\*Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

# Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi						
30™ Gold	Solo Air™	26	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	-	265 psi
		27.5 29	100							
		27.5 29	120	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	-	205 psi
30 Silver	Solo Air	26	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	-	265 psi
		27.5 29	100							
		27.5	120	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	-	205 psi
Bluto™	Solo Air	26	80 100 120	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi	-	200 psi
BoXXer® World Cup	Solo Air	26 27.5	200	50-65 psi	65-80 psi	80-95 psi	95-110 psi	110-125 psi	125+ psi	165 psi
Lyrik™	Solo Air	27.5 27.5B*	160							
		29 29B*/27.5+	150 160	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95+ psi	148 psi
		26	170							
	27.5 27.5B* 29 29B*/27.5+	170 180	35-45 psi	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85+ psi	148 psi	
	Dual Position Air™	27.5 27.5B*	160							
		29 29B*/27.5+	150 160	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi
27.5 27.5B*		170 180	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95+ psi	148 psi	

# Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi						
Pike®	Solo Air™	27.5 27.5B* 29 29B*/27.5+	120	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	163 psi
		29+								178 psi
	Solo Air™	27.5 27.5B* 29 29B*/27.5+ 29+	130 140	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi
		26 27.5 27.5B* 29 29B*/27.5+ 29+	150 160							148 psi
	Dual Position Air™	26 27.5 27.5B* 29 29B*/27.5+	150 160	45-65 psi	65-85 psi	85-105 psi	105-125 psi	125-145 psi	145+ psi	248 psi
		29+	150 160							55-65 psi
Pike DJ	Solo Air	26	100	100-115 psi	115-130 psi	130-145 psi	145-160 psi	160-175 psi	175+ psi	250 psi
			140	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	163 psi
Reba®	Solo Air	29 29B*/27.5+	80	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi	-	200 psi
		27.5 27.5B* 29 29B*/27.5+	100 120							

# Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi						
Recon™ Gold	Solo Air™	27.5 29	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	-	265 psi
			100 120	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	-	205 psi
Recon Silver	Solo Air	27.5 29	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	-	265 psi
		27.5 27.5 B* 29 29 B*/27.5+	100 120	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	-	205 psi
Revelation™	Solo Air	29 29B*/27.5+	120	65-85 psi	75-100 psi	85-115 psi	95-125 psi	125+ psi	-	190 psi
		27.5 27.5B* 29 29B*/27.5+	130 140							
		27.5 27.5B*	150							
RS-1™	Solo Air	27.5 29 29+	100 120	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi	-	200 psi
Sektor™ Gold	Solo Air	27.5 29	130 140 150	40-60 psi	60-75 psi	75-90 psi	90-105 psi	105+ psi	-	225 psi
Sektor Silver	Solo Air	27.5 27.5B* 29 29B*/27.5+	130 140	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	-	200 psi
		27.5B*	150							

# Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi						
Yari™	Solo Air™	27.5 27.5B* 29 29B*/27.5+	120	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi
			120	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	178 psi
		130 140	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi	
		150 160	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95+ psi	148 psi	
	Dual Position Air™	27.5 27.5B* 29 29B*/27.5+	170 180	35-45 psi	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85+ psi	148 psi
			150 160	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi
		27.5 27.5B*	170 180	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95+ psi	148 psi
FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes Add 10 psi						
SID®	Solo Air	29 29B*/27.5+	80 100	<70 psi	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi	195 psi
			100							
FORK	AIR SPRING	WHEEL	TRAVEL (mm)	-	<132 lbs (<60 kg)	132-155 lbs (60-70 kg)	155-176 lbs (70-80 kg)	176-198 lbs (80-90 kg)	>198 lbs (>90 kg)	MAX PSI
				E-Bikes Add 10 psi						
Paragon™ Gold	Solo Air	700c	50 65	-	80-90 psi	90-100 psi	100-125 psi	125-135 psi	135+ psi	165 psi



# Coil Spring Rates

FORK	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	
<b>30™ Silver</b>	Not Available	Silver X-Soft	Yellow Soft	Red Medium	Blue Firm	Black X-Firm
<b>Argyle™</b>	Yellow Soft	Red Medium	Blue Firm	Black X-Firm	Not Available	Pink XXX-Hart
<b>BoXXer®</b>	Not Available	Silver X-Soft	Yellow Soft	Red Medium	Blue Firm	Black X-Firm
<b>Domain™</b>						
<b>Domain Dual Crown</b>						
<b>Recon™ Silver</b>						
<b>Sektor™ Gold</b>						
<b>XC™ 30</b>						

# Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)		AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
30™ Gold	26	80	1 1/8 Aluminum		9mm Quick Release	39		453	185	680	58
		100						473			
	27.5	80	Tapered	1 1/8 Aluminum		42		468		710	
		100						488			
		120						508			
	29	80	Tapered			46 51		487		755	
100		507									
120		527									
30 Silver	26	80	1 1/8 Aluminum		9mm Quick Release	39		455	185	680	58
		100						475			
	27.5	80	Tapered	1 1/8 Aluminum		42		470		710	
		100						490			
		120						510			
	29	80	Tapered			46 51		489		755	
100		509									
Argyle™	26	100	1 1/8 Aluminum		20mm x 110mm	40		480	203	697	68
Bluto™	26	80	Tapered		15mm x 150mm	51		491	215	760	116
		100						511			
		120						531			
BoXXer®	26	200	1 1/8 Aluminum		20mm x 110mm	42		568	210	696	-
	27.5					48		581		720	
Domain™	26	180	1 1/8 Steel		20mm x 110mm	40		565	203	698	70

# Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)				AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Domain™ Dual Crown	26	200	1 1/8 Aluminum				20mm x 110mm	42		568	210	696	-
	27.5							48		581		720	
Lyrik™	26	170	Tapered				20mm x 110mm	40		545	215	698	70
	27.5	160					15mm x 100mm	42		552		714	66
		170								562			
		180								572			
	27.5B*	160					15mm x 110mm	42	46	552		714	81
		170								562			
		180								572			
	29	150					15mm x 100mm	51		561		752	66
		160								571			
		170								581			
		180								591			
	29B*/27.5+	150					15mm x 110mm	51		561		752	81
		160								571			
		170								581			
		180								591			
	Paragon™	700c					50	Tapered	1 1/8 Aluminum	1 1/8 Steel		1 1/8 Steel XL	9mm Quick Release
65			477										
Pike® DJ	26	100	Tapered				15mm x 100mm	40		482	215	694	66
		140								522			

# Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)	AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)		
Pike®	26	150	Tapered	15mm x 100mm	40		532	210	694	66		
		160					542					
	27.5	120			512							
		130			522							
		140			532							
		150			542							
		160			552							
		42 46			512							
	27.5B*	120			522	15mm x 110mm	42 46		215		714	81
		130			532							
		140		542								
		150		552								
		160		512								
	29	120		531	15mm x 100mm	46 51	210	752	66			
		130		541								
		140		551								
		150		561								
		160		571								

# Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)		AXLE		OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)		
Pike®	29B*/27.5+	120	Tapered		15mm x 110mm		51		531	210	752	81		
		130							541					
		140							551					
		150							561					
		160							571					
	29+	120							543	215	786	82		
		130							553					
		140							563					
		150							573					
		160							583					
Reba®	27.5	100	Tapered	1 1/8 Aluminum	9mm Quick Release	15mm x 100mm		42		487	710	62		
		120					507							
	27.5B*	100	Tapered			15mm x 110mm						487	712	81
		120					507							
	29	80	Tapered	1 1/8 Aluminum	9mm Quick Release	15mm x 100mm		46	51	486	215	755	62	
		100								506				
		120								526				
	29B*/27.5+	80	Tapered			15mm x 110mm		51		491	760	81		
		100								511				
		120								531				

# Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)	AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)	
Recon™ Gold	27.5	80	1 1/8 Aluminum	9mm Quick Release	42		469	200	710	62	
			Tapered								15mm x 100mm
		100	1 1/8 Aluminum	9mm Quick Release				489			200
			Tapered	15mm x 100mm							
		120	1 1/8 Aluminum	9mm Quick Release				509			200
			Tapered	15mm x 100mm							
	29	80	1 1/8 Aluminum	9mm Quick Release	46	51		486	753		
			Tapered	15mm x 100mm						488	
		100	1 1/8 Aluminum	9mm Quick Release				506			
			Tapered	15mm x 100mm						508	
		120						528			

# Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)		AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)			
Recon™ Silver	27.5	80	1 1/8 Aluminum		1 1/8 Steel	9mm Quick Release		42	466	203	710	62		
			Tapered		15mm x 100mm									
		100	1 1/8 Aluminum		1 1/8 Steel	9mm Quick Release							486	
			Tapered		15mm x 100mm									
		120	1 1/8 Aluminum				9mm Quick Release						506	
			Tapered				15mm x 100mm							
	27.5B*	80					9mm Quick Release		42	469	215	712	81	
		100	Tapered				15mm x 110mm							
		120	Tapered				15mm x 110mm							
	29	80	Tapered	1 1/8 Aluminum	1 1/8 Steel	9mm Quick Release		51		203	755	62		
						15mm x 100mm		46	51					
		100				9mm Quick Release		51						
						15mm x 100mm		46	51					
	29B*/27.5+	80					9mm Quick Release		42	489	215	760	81	
		100	Tapered				15mm x 110mm							
		120	Tapered				15mm x 110mm							

# Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)		AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)	
Revelation™	27.5	130	Tapered		15mm x 100mm	42		519	215	717	62	
		140						529				
		150						539				
	27.5B*	130			519			15mm x 110mm		529		
		140			539							
		150			539							
	29	120			15mm x 100mm	46	51	528		755	62	
		130			538							
		140			548							
	29B*/27.5+	120			15mm x 110mm	51		530		760	81	
		130						540				
		140						550				
RS-1™	27.5	100	Tapered Carbon		Predictive Steering™		42	215	710	62		
		120					487					
	29	100					42		51		506	751
		120					46		51		526	
	29+	100					51		526		780	82
		100					51		526			
SID®	27.5	100	Tapered	Tapered Carbon	15mm x 100mm	42		487	215	714	62	
			Tapered		15mm x 110mm							81
	27.5B*	100	Tapered		15mm x 110mm	42		487		714	81	
			Tapered		15mm x 110mm							
	29	80	Tapered	Tapered Carbon	15mm x 100mm	46	51	486		755	62	
		100	Tapered		15mm x 100mm	46	51	506				
	29B*/27.5+	80	Tapered		15mm x 110mm	51		491		755	81	
		100	Tapered					15mm x 110mm				51



# Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)			AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)									
Sektor™ Gold	27.5	130	Tapered			15mm x 100mm	42		519	215	717	62									
		140							529												
		150							539												
	29	130					46 51		538		755										
		140							548												
Sektor Silver	27.5	130	Tapered			15mm x 100mm	42		520	215	717	62									
		140							530												
	27.5B*	130				15mm x 110mm			46 51			520	752								
		140										530									
		150										540									
	29	130				15mm x 100mm						51		539	62						
		140					549														
	29B*/27.5+	130				15mm x 110mm	51				539			760							
		140							549												
	XC™ 30	27.5				80			Tapered					9mm Quick Release			470	185	710	62	
						100											42				490
						120						510									
29		80	46 51		489	755															
		100			509																

# Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)	AXLE	OFFSET (mm)		AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)	
Yari™	27.5	120	Tapered	15mm x 100mm	42	46	512	215	714	66	
		130					522				
		140					532				
		150					542				
		160					552				
		170					562				
		180					572				
	27.5B*	120		512							
		130		522							
		140		532							
		150		542							
		160		552							
		170		562							
		180		572							
	29	120		531	15mm x 100mm	51			531	752	66
		130		541							
		140		551							
		150		561							
		160		571							
		170		581							
		180		591							

# Configurations

FORK	WHEEL (in)	TRAVEL (mm)	STEERER TUBE (in)	AXLE	OFFSET (mm)	AXLE to CROWN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Yari™	29B*/27.5+	120	Tapered	15mm x 110mm	51	531	215	786	81
		130				541			
		140				551			
		150				561			
		160				571			
		170				581			
		180				591			
	29+	120				543			82
		130				553			
		140				563			
		150				573			
		160				583			

This publication includes a trademark from the following company:

BOOST™ is a trademark of Trek Bicycle Corporation.

# ***SRAM***®

*www.sram.com*



ASIAN HEADQUARTERS  
SRAM Taiwan  
No. 1598-8 Chung Shan Road  
Shen Kang Hsiang, Taichung City  
Taiwan R.O.C.

WORLD HEADQUARTERS  
SRAM LLC  
1000 W. Fulton Market, 4th Floor  
Chicago, Illinois 60607  
U.S.A.

EUROPEAN HEADQUARTERS  
SRAM Europe  
Paasbosweg 14-16  
3862ZS Nijkerk  
The Netherlands